

Tippers

Category	Specification	4038K
Engine		
	Engine Make/Model	Cummins ISLe 375 Euro-III
	Cylinder	6 inline
	Engine Aspiration	Turbo Inter-cooled
	Engine Displacement	8900 cc
	Fuel	Diesel
	Max. Torque	1550 Nm
	Max. Torque r/min	1300 r/min
	Output HP	380 HP
	Max. Power r/min	2100 r/min
Data		
	Geared Max. Speed	95 kmph
	Grade @ D/T (Max. Torque-1st Gr)(%)	40%
Transmission		
	1st Gear Ratio	14.39
and the second s	Drive	6x4
	Drive Axle Type	Hub Reduction
	Gearbox	Manual
THE STREET	Gearbox Make/Model	Eaton ES15409-DD
The state of the s	No. of Forward Gears	9
	Top Gear Ratio	1.00
Dimensions		1000
	Overall Length (mm)	8482 (with load body)
		2590
	Overall Width (mm) Overall Height (unladen) (mm)	3682 (with load body)
	Front Overhang (mm)	1482
	Rear Overhang (mm)	1095 (from rear most Axle centre)
the state white	Wheelbase (mm)	4570
	Turning Radius (mm)	9845
	Tank Capacity (Itrs)	260
Wheels		
	Spare Wheel Carrier	Yes
	Tyre Size	12R24
	Tyre Specification	\ Radial \
	Wheelrim Size	8.25x24
Weights		
Carry Server Server	Manufacturer's Gross Vehicle Mass (kg)	40000
	Manufacturer's Gross Combination Mass (kg)	
THE REST OF THE	Permissible Maximum Front Axle Mass (kg)	7500
	Permissible Maximum Rear Axle Mass (kg)	32000
	Unladen Front Axle Mass (kg)	5780
	Unladen Rear Axle Mass (kg)	8605
	Total Unladen Mass (kg)	14385
Pooto		
Seats	No of Socto	2
Stooring	No. of Seats	2
Steering	Stooring	Hydraulia Pawar aggisted
Cofety	Steering	Hydraulic Power assisted
Safety	Drakes Parking	Spring actuated on Rear Axle
	Brakes - Parking	
	Brakes - Service	Full Air Dual Circuit
ELECTRIC STATE OF THE	Electronic Brake Controls	ABS
STATE OF THE STATE	Engine Brake	Jake Brake
	Front Axle Suspension	Parabolic Leaf Springs
	Rear Axle/Bogie Suspension	Semi Elliptic Leaf Springs Bogie
Convenience	the second secon	
A WIRE BASES	Air-conditioner	Yes - HVAC
THE POST OF LEWIS	Tilt Mechanism	Yes
Load Body		the second of th
THE STREET STREET	Туре	Box with Tail door
	Size	18 Cu m