



XP201 轮胎压路机

XP201 轮胎压路机

XP201 轮胎压路机属自行式静作用压路机，适用于压实沥青路面、混凝土路面、基础层、次基础层及填方工程等，是道路建设、水利建设等不可缺少的压实设备。尤其对高等级公路的沥青面层的压实能获得其它压实机械无法达到的压实效果。

XP201 Pneumatic Roller

XP201 Pneumatic roller is the self-propelled roller, which is mainly suited for compaction works of the asphalt road, concrete road, base layer, sub-base layer and backfilling. It is the important compacting machine in the field of compacting road and irrigation works. It has the better compacting effect than the other compaction machine in the field of compacting asphalt surface layer.



XP201


轮胎压路机 PNEUMATIC ROLLER

主要技术参数

MAIN TECHNICAL SPECIFICATIONS

车型	Type	Unit	XP201
最小工作质量	Min.working mass	kg	12000
最大工作质量	Max.Working mass	kg	20000
接地比压	Rolling pressure	kpa	200~400
行驶速度	Driving speed		
I 速	I speed	km/h	0~8
II 速	II speed	km/h	0~20
理论爬坡能力	Gradeability	%	20
最小转弯半径	Min.Turning radius	mm	8000
最小离地间隙	Min.Clearance	mm	290
压实宽度	Compacting width	mm	2250
轮胎重叠量	Overlapping of front & rear tyre	mm	50
轮胎规格	Tyre specification		11.00-20-16PR
轮胎数量	Numbers of tyre		4-tyre front & 5-tyre back
发动机	Engine		
型号	Model		Cummins 4B3.9(Tier2)
型式	Type		water cooled, turbo charging
最大功率	Max.Power@2200r/min	kW	93
总体尺寸(外形尺寸)	Total size(contour size)		
长度	Length	mm	4896
宽度	Width	mm	2363
高度	Height	mm	3200

本产品随着技术进步不断改进，如有修改，恕不另行通知。样本图片与实物不符的，以实物为准。
Under our policy of continuous product development and improvement, we reserve the right to change specifications and design without prior notice.



XCMG Exclusive Agent in Qatar.

AL HAMAD AUTOMOBILES COMPANY WLL,
AL AZIZIYA, SALWA ROAD, P.O BOX: 31531,
DOHA, QATAR.
TEL: +974 44510606 / 44510707 FAX: +974 44686327
Email: info@alhamadautomobiles.com.qa